




ArmstrongFlooring™

Curdlee®





K866-203

Apricot



K866-201

Light Beige



K866-202

Plume



K866-204

Wood



K866-205

Plum



K866-007


Deep Tone






K866-005

Dawn Moon



K866-006

Rock




K866-003

Song of Moon




K866-004

Hazy Moon




K866-604

Tranquil




K866-601

Glacier



K866-605

Sunlit River



K866-602

Cirrus



K866-603

Blue Frog



K866-001 Shadow



K866-701 Lavender




K866-002 Clouds



K866-702 Pink Sakura




K866-703 Sunkist




K866-501 Willow Creek




K866-504 Lime Green



K866-502 Turquoise



K866-503 Spring Grass



Environmental Advantages



Reliable Raw Materials

- Comply with REACH regulations
- Phthalate-free plasticizers
- Formaldehyde-free
- Comply with EN71-3, Migration of Certain Elements



Life Cycle Assessment (LCA)

- Based on a comprehensive evaluation of the product's entire life cycle
- Environmental Product Declaration (EPD)
- EPD is an essential documentation to earn product credit for certifications like LEED and WELL, and it is a crucial criterion for selecting low-carbon, transparent materials.



Low VOC Emissions for Improved Indoor Air Quality

- Agbb 28 days TVOC <math>< 10 \mu\text{g}/\text{m}^3</math>
- Formaldehyde-free
- FloorScore certified



Technical Data

Characteristics	Standard	Unit	Result
Type of flooring	ISO 10581/EN 649		Polyurethane coated Homogeneous Sheet
Material			Polyvinyl chloride
Coating			TRUESHIELD XP
Safety criteria			
TVOC after 28 days	ISO 16000-6		< 10µg/m³
DOP Content	EN 14372		N.D.
Migration of Certain Elements	EN 71-3		Pass
Performance behaviour			
Roll width	ISO 24341/EN 426	m	2
Roll length	ISO 24341/EN 426	m	15/20
Overall thickness	ISO 24341/EN 428	mm	2.0
Dimensional stability	ISO 23999/EN 434	-	X (horizontal): 0.4% Y (vertical): 0.4%
Wear resistance	EN660-2/EN649	group	T
Chemical Resistance	ISO 26987/EN 423		Grade 0: No Stain
Color fastness	ISO 105-B02	rating	≥ 6
Static electrical charge	EN 1815	KV	≤ 2.0
Classification			
Domestic	EN 685	class	23 heavy duty
Commercial	EN 685	class	34 very heavy duty
Industrial	EN 685	class	43 heavy duty
Additional property			
Castor Chair  ✓	Underfloor Heating  ✓	Anti-bacteria  ✓	
Antistatic Behaviour  ✓	Chemical Resistance  ✓		



Website: www.armstrongflooring.asia
 Hotline: 400-606-0866

YS-SF-Curdlee® - 1224-PRC Printed in China

The above information is for reference only. Our company reserves the right to modify the details mentioned at any time.
 For all contents in this manual, our company reserves all legal rights and final interpretation rights.